




## Agenda

- I. CALL TO ORDER: 6:00 PM
  
- II. PUBLIC FORUM
  
- III. ACTION ITEMS
  - A. Proposed Road Diet on North Main Street
  
- IV. COMMISSIONER COMMENTS
  
- V. ADJOURN: 8:00 PM


**Next meeting scheduled for April 21, 2011 @ 6:00 pm**  
**Next joint meeting scheduled for April 26, 2011 @ 6:00 pm**

**Note to Commissioners: Call Nancy Slocum at 552-2420 or [slocumn@ashland.or.us](mailto:slocumn@ashland.or.us) if you can not attend the meeting.**



*In compliance with the Americans with Disabilities Act, if you need special assistance to participate in this meeting, please contact the Public Works Office at 488-5587 (TTY phone number 1 800 735 2900). Notification 48 hours prior to the meeting will enable the City to make reasonable arrangements to ensure accessibility to the meeting (28 CFR 35.102-35.104 ADA Title I).*



Typical Tree-Lane Cross Section



Excerpts from ODOT Standard Drawing RD706  
Concrete TRAFFIC SEPARATOR, TYPE B




**N MAIN STREET ROAD DIET  
FOR DISCUSSION PURPOSES ONLY**



**Figure  
1**

H:\profile\10633 - City of Ashland TSP Update\dwgs\design\10633FD02.dwg Mar 09, 2011 - 3:13pm - jsommerville Layout Tab: Fig01



SEE BELOW LEFT



SEE NEXT PAGE



**N MAIN STREET ROAD DIET  
FOR DISCUSSION PURPOSES ONLY**



**Figure  
2**



H:\profile 10633 - City of Ashland TSP Update\dwgs\design\10633FD02.dwg Mar 09, 2011 - 3:15pm - jsommerville Layout Tab: Fig02



**N MAIN STREET ROAD DIET  
FOR DISCUSSION PURPOSES ONLY**






**Figure  
3**



**N MAIN STREET ROAD DIET  
FOR DISCUSSION PURPOSES ONLY**




**Figure  
4**



**N MAIN STREET ROAD DIET  
FOR DISCUSSION PURPOSES ONLY**



**Figure  
5**



**N MAIN STREET ROAD DIET  
FOR DISCUSSION PURPOSES ONLY**



**Figure  
6**

# ROAD DIET FAQ SHEET

## Why try a temporary road diet?

To try-out a concept that has the potential to improve safety and better serve pedestrians and bicyclists. A temporary road diet provides the opportunity to determine how well the concept works and if there is public support prior to making significant investments in more permanently changing the roadway.

## Why would the City want to reduce the number of lanes on N. Main Street?

### IMPROVED SAFETY

Nationally published research indicates converting a four-lane roadway such as North Main Street to a three-lane cross-section (as suggested for North Main Street) reduces the total number of crashes along the roadway by 25% to 33%<sup>1</sup>.

North Main Street includes one of the top candidate intersections in Ashland for reducing crashes – the Hersey Street-Wimer Street/North Main Street intersection. The crashes that occur at and near that intersection as well as others along North Main Street tend to be related to vehicles making left-turns from North Main Street to the side streets and from the side streets on to North Main Street. The existing 4-lane configuration (2 lanes in each direction) requires vehicles turning left off of North Main Street to stop in a through lane to wait for a gap in traffic to turn left. This increases the risk for rear-end crashes as well as turning crashes when drivers rush to fit into a gap in traffic that is too short. Vehicles turning off of North Main Street onto a side street also have to look for a gap in two lanes of on-coming traffic, which can result in misjudgments. Vehicles turning left from the side streets on to North Main Street must watch four lanes of traffic to determine when it is safe to turn left. Misjudgments result in angle and turning crashes.

The three lane configuration will provide left-turn lanes for vehicles turning left off of North Main Street to reduce the likelihood of rear-end crashes. Vehicles turning off of Main Street will also only need to look for gaps in one lane of on-coming traffic reducing the risk of misjudging gaps. The

---

<sup>1</sup> American Association of State Highway and Transportation Officials (AASHTO). *Highway Safety Manual*. 2010.

three lane configuration will also make it easier for vehicles turning left on to North Main Street from the side street to determine if there is an adequate gap since drivers will be concerned with fewer lanes of traffic compared to today.

#### REDUCED TRAVEL SPEEDS

North Main Street currently has a posted speed limit of 35 miles per hour south of the Southern Pacific Railroad overcrossing and 25 miles per hour south of Grant Street. However, it is believed that the four lane cross section results in travel speeds in excess of the posted speed limit. This will be verified as part of the on-going traffic analysis for the road diet. Narrowing the cross-section to three lanes and adding features such bike lanes creates a “tunnel effect” that naturally reduces travel speeds. Case studies from previous road diets in the United States indicate in some cases vehicle speeds reduced by 18% and vehicles over the speed limit reduced by 32%<sup>2</sup>.

#### **What about emergency vehicles?**

Ashland Police, Fire and emergency services (ambulances) are involved in the discussions of reducing North Main Street to three lanes. They have seen and commented on the proposed change and they are comfortable with testing the three lane scenario. Providing emergency service and response along North Main Street as a three-lane street would be similar to the situations they encounter when providing service on East Main Street (currently two-lanes with bicycle lanes) as well as other two- and three-lane streets in Ashland.

#### **What about evacuation needs?**

In the event of the need to evacuate Ashland, North Main Street could be converted to as many as three lanes traveling outbound (north) or it could be converted to two lanes outbound while providing one lane for southbound travel. The same type of arrangement could be made for the existing four-lanes. The City and/or emergency personnel would coordinate and manage such a situation if one arose.

---

<sup>2</sup> Road Diet Handbook: Setting Trends for Livable Streets, Second Edition. 2007.

## **What will that do to traffic congestion now?**

Traffic congestion will increase slightly in some areas, primarily at the north and southbound approaches to the signalized intersections, but the amount of time it takes to travel the length of the corridor under consideration for the road diet will remain relatively the same.

## **What about 25 years from now when traffic volumes increase?**

A 25 year traffic analysis was conducted at the Maple Street and Wimer-Hersey Street intersections to determine the impact of the road diet on existing and future (year 2034) traffic conditions. Preliminary results indicate that operations along North Main Street are not deteriorated significantly over the 25 year period.

## **How will the road diet affect heavy truck traffic on Hersey Street?**

Heavy trucks will continue to use North Main Street as well as Hersey Street with the road diet. The intersection of North Main Street and Wimer-Hersey Street will be reconfigured to accommodate heavy truck turning movements through the intersection. Left-turn movements from North Main Street onto Hersey Street will be permitted. Left-turn movements from North Main Street onto Wimer Street will be prohibited. Similarly, left-turn movements from Wimer Street and Hersey Street onto North Main Street will be prohibited. The purpose of these left-turn restrictions during the temporary road diet is to reduce conflicts and therefore crashes at the Hersey-Wimer Street/North Main Street intersection, which due to the history of crashes at that location, is now a safety focus intersection where the City is working to reduce crashes.

## **How will the road diet improve safety for bicyclists?**

North Main Street currently does not have designated bicycle facilities north of Helman Street. The provision of north-south striped bicycle lanes on the roadway shoulder will provide separation between vehicles and bicyclists reducing the potential for conflicts and improving bicycle safety. Nationally published research indicates installing bicycle lanes on an urban arterial such as North Main Street tends to reduce not only vehicle-bicycle crashes but also total crashes on the roadway<sup>3</sup>. Buffered bicycle lanes would increase the separation as well as riding comfort for bicyclists.

---

<sup>3</sup> American Association of State Highway and Transportation Officials (AASHTO). Highway Safety Manual. 2010.

---

## **Why test this during the summer?**

Testing the Road Diet during the summer months allows us to see if the three-lane configuration will work for Ashland year round. If we, the community, like how it works during the summer we can feel confident that it will work year round because the summer is when we experience the highest traffic volumes on North Main Street.

In order to do this project as a test, we need to be able to remove it before the weather becomes wet in the fall. The project consists primarily of restriping which can only be done in dry weather. We need to evaluate the new configuration for several months and ensure we have the opportunity to return it to four lanes before the rainy season.

## **Why doesn't ODOT add bike lanes by widening the highway?**

For most of this corridor, there is no right-of-way available to widen the roadway for bicycle lanes or to add a center left-turn lane and keep the existing four lanes. ODOT standards require that they add bicycle lanes when they are modernizing a roadway; however, ODOT would not be widening this segment of Main Street to provide additional vehicle capacity in the foreseeable future because the additional capacity is not warranted and the right-of-way is not available to do so. Even if purchasing right-of-way were going to be considered, several properties along the corridor are nationally registered historic sites and many are identified by the city as historically significant and not feasible to obtain additional right-of-way.

# CITY OF ASHLAND

March 24, 2011

RE: DISCUSSION OF NARROWING NORTH MAIN STREET TO THREE LANES

Dear Ashland Neighbor:

As you may have heard, the Transportation Commission, the Planning Commission and the Public Works Department are currently updating the City's Transportation System Plan (TSP). The update includes a proposal to temporarily narrow North Main Street from Helman Street north to Jackson Road from four lanes to three lanes. The proposal, commonly referred to as a "road diet," is being considered because nationally published research has found that road diets can reduce crashes 24% to 33% and have been found to reduce travel speeds. The proposal also creates the opportunity to add bike lanes on both sides of the street. (Please see the attached Road Diet Fact Sheet for more information.) The proposed North Main Road Diet Striping plan can be viewed online at [http://www.ashlandtsp.com/statics/draft\\_documents](http://www.ashlandtsp.com/statics/draft_documents).

Before the City Council makes a decision on the proposal to conduct this pilot program, the Transportation Commission will take public testimony and make a recommendation to the City Council. If you would like to comment on the proposal, please feel free to attend the meeting on Thursday, March 31<sup>st</sup> beginning at 6:00 pm. The meeting will be held at the Council Chambers, 1175 East Main Street. Comments can also be emailed to [olsonj@ashland.or.us](mailto:olsonj@ashland.or.us).

This notice was mailed to property owners only. If your property is leased to a third party, please feel free to forward this information to them. If you wish additional information, please call our office at 541 488-5347.

Sincerely,



James H. Olson  
Transportation Commission Staff Liaison

cc: file



# **Road Diet FAQ Sheet**

## **Why would the City want to reduce the number of lanes on N. Main Street?**

### Improved safety

Nationally published research (American Association of State Highway and Transportation Officials. Highway Safety Manual, 2010) indicates converting a four-lane roadway such as North Main Street to a three-lane cross-section reduces the total number of crashes along the roadway by 25% to 33%. This section of North Main Street includes one of the top candidate intersections in Ashland for reducing crashes – the Hersey Street-Wimer Street/North Main Street intersection. The crashes that occur at and near that intersection as well as others along North Main Street tend to be related to vehicles making left-turns from North Main Street to the side streets and from the side streets on to North Main Street. The existing 4-lane configuration (2 lanes in each direction) requires vehicles turning left off of North Main Street to stop in a through lane to wait for a gap in traffic to turn left. This increases the risk for rear-end crashes as well as turning crashes when drivers rush to fit into a gap in traffic that is too short. Vehicles turning off of North Main Street onto a side street also have to look for a gap in two lanes of on-coming traffic, which can result in misjudgments. Vehicles turning left from the side streets on to North Main Street must watch four lanes of traffic to determine when it is safe to turn left. Misjudgments result in angle and turning crashes.

The three lane configuration will provide left-turn lanes for vehicles turning left off of North Main Street to reduce the likelihood of rear-end crashes. Vehicles turning off of Main Street will also only need to look for gaps in one lane of on-coming traffic reducing the risk of misjudging gaps. The three lane configuration will also make it easier for vehicles turning left on to North Main Street from the side street to determine if there is an adequate gap since drivers will be concerned with fewer lanes of traffic compared to today.

### Reduced Travel Speeds

North Main Street currently has a posted speed limit of 35 mph south of the Southern Pacific Railroad overcrossing and 25 mph south of Grant Street. However, it is believed that the four lane cross section results in travel speeds in excess of the posted speed limit. This will be verified as part of the on-going traffic analysis for the road diet. Narrowing the cross-section to three lanes and adding features such bike lanes creates a “tunnel effect” that naturally reduces travel speeds. Case studies from previous road diets in the United States indicate in some cases vehicle speeds reduced by 18% and vehicles over the speed limit reduced by 32%.

## **What will a “road diet” do to traffic congestion?**

Traffic congestion will increase slightly in some areas, primarily at the north and southbound approaches to the signalized intersections, but the amount of time it takes to travel the length of the corridor under consideration for the road diet will remain relatively the same. A 25 year traffic analysis was conducted at the Maple Street and Wimer-Hersey Street intersections to determine the impact of the road diet on existing and future (year 2034) traffic conditions. Preliminary results indicate that congestion along North Main Street will not increase significantly over the 25 year study period.

## **Why test this during the summer?**

Testing the Road Diet during the summer months allows us to see if the three-lane configuration will work for Ashland year round. If we, the community, like how it works during the summer we can feel confident that it will work year round because the summer is when we experience the highest traffic volumes on North Main Street. In addition, in order to do this project as a test we need to be able to remove it before the weather becomes wet in the fall. The project consists primarily of restriping which can only be done in dry weather. We need to evaluate the new configuration for several months and ensure we have the opportunity to return it to four lanes before the rainy season.

## **Why doesn't ODOT add bike lanes by widening the highway?**

For most of this corridor, there is no right-of-way available to widen the roadway for bicycle lanes or to add a center left-turn lane and keep the existing four lanes. ODOT standards require that they add bicycle lanes when they are modernizing a roadway; however, ODOT would not be widening this segment of Main Street to provide additional vehicle capacity in the foreseeable future because the additional capacity is not warranted and the right-of-way is not available to do so. Even if purchasing right-of-way were to be considered, several properties along the corridor are nationally registered historic sites and many are identified by the city as historically significant and not feasible to obtain additional right-of-way.

*An expanded fact sheet can be found at [http://www.ashlandtsp.com/statics/draft\\_documents](http://www.ashlandtsp.com/statics/draft_documents).*